

## **Overview**

The CO8CW is a 2-way speaker designed with an 8" compact coaxial driver, providing a small footprint for high SPL.

With an Ingress Protection rating of IP56, the CO8CW has been treated to be highly weather resistant, particularly to dust and high-pressure water.

The Coliseum CO8CW is a perfect sound solution for sports fields, restaurant patios, and wherever waterproof speakers are required.

## **Features**

- 150 Watts
- 8-inch woofer with 2-inch voice coil
- 1-inch compression driver
- 100° x 100° HF dispersion
- Injection Molded plastic cabinet construction
- Highly weather-resistant IP56 rating
- All metal U bracket included



System Type	2-way
Powered or Passive	Passive
Program Power (watts)	150
Biampable	No
Nominal Impedance (Ohms)	8 or 70/100 Volt
Max SPL (dB)	124dB continuous
Frequency Response (Hz +/- 3dB)	80 - 18k (Hz +/-3dB)
Crossover Frequency (Hz)	2.5kHz Passive
LF Driver	8"
HF Driver	1"
HF Horn	Injection Molded Plastic
HF Dispersion (°H x °V)	100° x 100°
Inputs	Screw Terminal
Outputs	Screw Terminal
Controls	37.5w / 75w / 150w / off /
	8 Ohm
Included Hardware	Yoke Bracket
Enclosure Materials	Injection Molded Plastic
Baffle Material	Injection Molded Plastic
Grille	Perforated Steel
Dimensions (DWH xbackW, inches)	13.7 x 11.87 x 11.88
Dimensions (DWH xbackW, cm)	$34.8 \times 30 \times 30.2$
Weight (lbs/kg)	24.25 / 11
Box Dimensions (LxWxH, inches)	19 x 16.5 x 18.5
Box Dimensions (LxWxH, cm)	48 x 42 x 47









