

C12CW

12-INCH LOUDSPEAKER SYSTEM



Overview

The C12CW is a 2-way speaker designed with a 12" coaxial driver, providing a small footprint for high SPL.

With an Ingress Protection rating of IP56, the C12CW has been treated to be highly weather resistant, particularly to dust and high-pressure water.

The Coliseum C12CW is a perfect sound solution for sports fields, restaurant patios, and wherever waterproof speakers are required.

Features

- 300 Watts
- 12-inch woofer with 3-inch voice coil
- 1-inch compression driver
- 80° x 80° HF dispersion
- Injection Molded plastic cabinet construction
- Highly weather-resistant IP56 rating
- All metal U bracket included



Specifications

System Type	2-way
Powered or Passive	Passive
Program Power (watts)	300
Biampable	No
Nominal Impedance (Ohms)	8 or 70/100 Volt
Max SPL (dB)	129dB continuous
Frequency Response (Hz +/- 3dB)	55 - 18k (Hz +/-3dB)
Crossover Frequency (Hz)	2.2kHz Passive
LF Driver	12"
HF Driver	1"
HF Horn	Injection Molded Plastic
HF Dispersion (°H x °V)	80° x 80°
Inputs	Screw Terminal
Outputs	Screw Terminal
Controls	50w / 100w / 200w / off / 8 Ohm (300 Watts)
Included Hardware	Yoke Bracket
Enclosure Materials	Injection Molded Plastic
Baffle Material	Injection Molded Plastic
Grille	Perforated Steel
Dimensions (DWH xbackW, inches)	17 x 16 x 11.88 x 16.2
Dimensions (DWH xbackW, cm)	44.3 x 40.7 x 41.1
Weight (lbs/kg)	43.65 / 19.8
Box Dimensions (LxWxH, inches)	19 x 16.5 x 34
Box Dimensions (LxWxH, cm)	48 x 42 x 87

Specifications subject to change without notice

