## Overview

This 2 x 15-inch / 1-inch, 1600 watt loudspeaker delivers amazing punch and extended low frequency response.

Ideal for use with or without a subwoofer, the E215's extended bottom end can easily cover many club applications on its own. The rotatable 80° x 50° horn means high frequency dispersion can be tailored to suit the cabinet's placement or application.

Integrated flypoints mean the E215 can be easily used in any install, touring or club rig.

The E215 is perfect for application in medium to large venues, especially when used with an optional EP215 processor and/or élite subwoofer for extended low frequency support.

E215 - Black Ozite (Carpet) Finish E215B - Black Ultrathane (Painted) Finish

## **Features**

- 2400 Watt Full Range Loudspeaker (1200 Watts Program)
- 2x15-inch Woofers / 1-inch Compression Driver
- Max SPL 134dB Peak (131dB Continuous)
- Designed for Full Range Front-of-House Performance
- 80° x 50° ABS Rotatable Custom Waveguide Horn
- Advanced PTC<sup>™</sup> High Frequency Driver Protection
- 2 x Speakon<sup>™</sup> and 2 x 1/4-inch Parallel Inputs
- Integrated All Metal Speaker Standmount Adaptor
- Solid 5/8-inch (15mm) Birch Plywood Construction
- Made in Canada



## Specifications

-	
System Type	Two - Way
Active or Passive	Passive
Program Power (Watts)	1200 Watts (2400 Peak / 600 Continuous)
Biampable	Yes
Nominal Impedance (Ohms)	4
Sensitivity (dB @1Watt/1m)	100
Max SPL (dB)	134dB Peak (131dB Continuous)
Frequency Response (Hz +/- 3dB)	55 - 20k
Crossover Frequency (Hz)	1000
Driver Configuration	2 x 15-inch / 1-inch
HF Horn	ABS Waveguide
HF Dispersion (°H x °V)	80 x 50 (Rotatable)
HF Protection	PTC <sup>TM</sup>
LF Driver(s)	2 x 15-inch
Inputs - 1/4" Jacks	2
Inputs - Speakon 4-pin	2
Flying Hardware	3/8-inch x 9 (All Corners)
Wheels	2
Bar Handles	2 Side, 1 Corner
Enclosure Materials	15mm (5/8inch) 11-ply Russian Birch
Grille	Perforated Metal
Covering / Finish	Black Ozite (Carpet)
Optional Covering / Finishes	Black Ultrathane Paint (E215B)
Processor (optional)	EP215
Dimensions (DWH xbackW COM inches)	23 x 22 x 46 x 11
Dimensions (DWH xbackW COM cm)	59 x 56 x 117 x 28
Weight (lbs/kg)	117.3 / 53.2

Specifications subject to change without notice