

## **Overview**

Weighing in under 15 pounds (6.6 kg), the EXM70 uses two high quality long excursion 6.5-inch woofers and a studio monitor quality soft dome tweeter to deliver quality full range tone from as small a footprint as physically possible.

The integrated three channel 70-watt passively cooled amplifier allows direct connection of instruments, media players or microphones to the system without an additional external mixer. Individual volume and tone controls for each input channel, and a master digital effect processor ensure the EXM70 is ready for any solo or duo performance.

## Features

- 140 Watts (Peak) 70 Watts (Program)
- 2 x 6.5-inch woofers
- I-inch compression driver
- Integrated 3 channel mixer
- ABS cabinet construction
- Bluetooth streaming
- Made in Canada



## **Specifications**

System Type	2-way
Powered or Passive	Powered
Program Power (watts)	1040 watts peak
	70 watts program
Max SPL (dB)	115dB continuous
Frequency Response (Hz +/- 3dB)	90 - 20k (Hz +/-3dB)
Crossover Frequency(Hz)	2.2kHz
LF Woofer	2 x 6.5″
HF Driver(s)	1″ Soft Dome
HF Dispersion (°H x °V)	60° x 60°
Power Cable	Yes(Detachable IEC)
Mixer Controls	Level, Shape, Effects
Level Controls	Channels 1-3 and Master
EQ Controls	Tone
Inputs	2 x Combi-jack (XLR / 1/4
	1 x XLR(CH 3)
	1 x 1/8″ TRS Stereo Jack
	Bluetooth
Other Features	LINK In/Out
	Digital Effects
Bar Handles	1 x Back (Integrated)
Pole Mount Adapter (1 3/8-inch/3.5cm)	1 Bottom
Enclosure Materials	ABS Cabinet
Grille	Powdered Coated
	Perforated Steel
Dimensions(DWH xbackW, inches)	17.5 x 7.75 x 8
Dimensions (DWH xbackW, cm)	44.5 x 19.7 x 20.25
Weight (lbs/kg)	16.3 / 7.4
Box Dimensions (LxWxH, inches)	10.2 x 20 x 11.4
Box Dimensions(LxWxH, cm)	26 x 50 x 29

orkvill

Specifications subject to change without notice



yorkville.com