

YSM5-2

5-INCH POWERED STUDIO MONITOR



Overview

Yorkville Sound's YSM SERIES 2 Powered Studio Monitors are engineered to deliver the uncompromising clarity your mixes demand. Designed with project and professional studios in mind, the YSM5-2 has been developed to be the best sounding monitor in its class.

The YSM5-2 features 1-inch silk diaphragm neodymium dome tweeters. These tweeters blend seamlessly into the specially designed low diffraction wave guide which is integrated into the front baffle. The edges of the wave-guide perfectly couple the tweeter with the woofer, reducing sonic anomalies normally associated with driver/tweeter proximity.

The woofer and tweeter have been perfectly time aligned to eliminate any phase irregularities usually associated with 2-way designs.

Features

- 50 Watts
- 5-inch woofer
- 1-inch Silk Neodymium dome tweeter
- High and Low Frequency adjust controls
- Volume Control

Specifications

System Type	2-way
Powered or Passive	Powered
Program Power (watts)	50 watts
Max SPL (dB)	105dB continuous
Frequency Response (Hz +/- 3dB)	50 - 22k(Hz +/-3dB)
Crossover Frequency (Hz)	2.1KHz
LF Woofer	5"
HF Driver(s)	1" Silk Neodymium dome
Power Cable	Yes (Detachable IEC)
Level Controls	Volume
EQ Controls	HF and LF Adjust
Inputs	1 x 1/4" TRS Balanced 1 x XLR Balanced 1 x RCA Unbalanced
Enclosure Materials	MDF ABS Baffle
Covering / Finish	Textured Vinyl
Dimensions (DWH xbackW, inches)	9.5 x 7.5 x 11.5
Dimensions (DWH xbackW, cm)	24.13 x 19.05 x 29.21
Weight (lbs/kg)	11 / 5.0
Box Dimensions (LxWxH, inches)	13 x 11 x 15
Box Dimensions (LxWxH, cm)	33 x 27 x 38

Specifications subject to change without notice

