

**YX****Passive Series****YX10**

Overview

The YX10 delivers maximum performance in the most compact loudspeaker available in the YX Series. Engineered in North America, the YX10 benefits from Yorkville's forty plus years of PA enclosure design experience in the creation of this ultra compact general purpose passive loudspeaker enclosure.

The YX10 cabinet uses a single 10-inch driver and an injection molded 100 x 30 degree horn with 1-inch throat and 1.4-inch neodymium compression driver. Yorkville's tried and true dual-bulb CTL™ protection system protects the horn driver's aluminum diaphragm ensuring unmatched reliability in the field. The YX10 is built road-ready with easy-to-clean, durable black carpet covering, solid internal plywood bracing and reinforced internal component mounts.

Designed with working musicians in mind, the YX10 offers rugged 5/8-inch plywood cabinet construction, all metal bar handles, metal input plate, integrated speaker mounts and a custom punched, perforated metal grille to protect the speaker components. A modified trapezoidal shape ensures the YX10 can function equally as well as a front-of-house or monitor speaker.



Features

- 200 Watt Full Range Loudspeaker
- 10-inch Woofer
- 1-inch Compression Driver (1.4-inch Voicecoil)
- Designed for Front-of-House or Monitor Applications
- 100° x 30° Injection Molded ABS Waveguide Horn
- Innovative Dual Bulb CTL™ High Frequency Driver Protection
- 2 x Speakon™ and 2 x 1/4-inch Parallel Inputs
- Integrated All Metal Speaker Standmount Adaptor
- Solid 5/8-inch (15mm) Plywood Construction

**YX****Passive Series****YX10**

Specifications

System Type	2-Way
Active or Passive	Passive
Program Power (Watts)	150
Biampable	No
Nominal Impedance (Ohms)	8
Sensitivity (dB @1Watt/1m)	97
Max SPL (dB)	119
Frequency Response (Hz +/- 3dB)	70 - 20k
Crossover Frequency (Hz)	2k
Driver Configuration	10 inch / 1.4 inch
HF Driver(s)	1.4 inch Aluminum (1 inch Throat)
HF Horn	Injection Molded ABS
HF Dispersion (°H x °V)	100 x 30
HF Protection	CTL™
LF Driver(s)	10 inch Ceramic
LF Program Power(Watts)	150
Inputs - 1/4" Jacks	2
Inputs - Speakon 4-pin	2
Corners	Metal
Feet	Plastic Glides
Bar Handles	1 (Side)
Pole Mount Adapter (1 3/8"-3.5cm)	Yes
Enclosure Materials	15mm (5/8inch) Plywood
Grille	Custom Punched Black Perforated Metal
Covering / Finish	Black Ozite
Dimensions (DWH xbackW, inches)	12 x 13.5 x 19 x 5.75
Dimensions (DWH xbackW, cm)	30.5 x 34.3 x 48.3 x 14.6
Weight (lbs/kg)	24 / 10.9

Specifications subject to change without notice